

## RQ-005 – 520bar Water Jetter



### Key Features:

- Industry recognised standard cleaning tool.
- Can be adapted to use as a fluid injection unit.
- Robust, easy to use and easy to fix pumps.

### WHATS INCLUDED

520bar Jetting System.  
ROV Handle and Point Jetting Nozzle.  
All Operational Hoses.  
Suction Filter.  
Operations Manual.  
Certificate Pack.

### OPTIONS

Spares Kit.  
Dual Nozzle Lance.  
Nozzle kit; Flat Jetting Nozzle and Rotating Nozzle.  
ROV handle options; D-Type, Fishtail, T-bar.

### Description

The High-pressure water jetting system is based around the industry standard Dynaset pump. No other pump gives the same power and reliability.

The pump can be connected to any subsea reservoir by the suction port (12 JIC / 3/4" BSPF) or filter.

The standard high-pressure jetting system has a pressure range from 0.5 - 520 Bar.

## RQ-005 – 520bar Water Jetter

Overall Specifications	
Weight in Air	32kg
Weight in Water	29kg
Dimensions	L300 x W200 x 230mm
Suitable Media	Sea Water, Glycol, Hydraulic Oil
Input / Outputs	
Max Input Pressure	210 BAR (3,000 PSI)
Max Input Flow	30-60 LPM
Max Output Pressure	520 BAR (7,500 PSI)
Max Output Flow	30 LPM
Hydraulic Connections	
Pressure	8 JIC
Return	8 JIC
Pilot	4 JIC
Suction	12 JIC / ¼" BSPF