

## RQ-022-3.2 – Hydraulic Fluid Compensators



### Key Features:

- Flexible Mounting options.
- Can be connected in a series for increased volume.
- Level Sensor Options.
- Pressure Relief Valve.

### WHATS INCLUDED

Compensator.  
Operations Manual.  
Certificate Pack.

### OPTIONS

Spares Kit.  
Level Sensor.

### Description

Our compensators are designed to have a small footprint with ease for mounting. With built in Heli-coils on each side of the main body the compensator can be mounted without any additional bracketry.

They are designed to provide submerged vehicles with a positive pressure of incompressible fluid to protect them against seawater ingress.

Built with a corrosion resistant plastic and with the option of a level sensor these units are ideal for compensating ROV system components.

Our standard unit is 3.2Litres however we can provide tailored solutions if required.

## RQ-022-3.2 – Hydraulic Fluid Compensators

Overall Specifications	
Weight in Air	8kgs (empty) 11.5kg (Full)
Weight in Water	5.5kg Full
Dimensions	L308 x W194 x H194mm
Max Pressure	15 PSI
Volume	3.2L
Hydraulic Ports	
Fill	4 JIC
Bleed	4 JIC
Pressure Out	8 JIC
Blanked	2 x 3/8" BSP & 3 X 1/2" BSP